Dd	B	$D  d   d_1 \\ d_2  D_2$								
Width (B)	17 mm									
ClosureRubber Seal Non-ContactRing Material52100 Chrome SteelBall Material52100 Chrome Steel										
						Brand	FAG B			
						Radial Clearance Normal				
Lubrication	L038 Mobil Polyrex EM Grease									
Dynamic Load(Cr)	5035.72 lbs									
Bore Diameter (d)	25 mm									
Series 6305		]								
Static Load Cap (C0r)	2562.82 lbs									
0.D. (D)	62 mm		COMPONENT	METRIC SERIES S	SEALED					
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	<b>6305–2RSR</b> <b>FAG</b> 25 Mm X 62 Mm X 17 Mm, Single Row Radial, Deep Groove Ball Bearing, Two Non Contact Rubber Seals		UNIT					
					SHEET					