| $\left  \begin{array}{c} \hline \\ \hline $ |  |  |   |                 |                |
|---|--|--|---|-----------------|----------------|
| Bore Diameter (d)   | 40 mm  |  |   |                 |                |
| Outside Diameter (D)  | 90 mm  |  |   |                 |                |
| Width (B) 23 mm   |  |  |   |                 |                |
| Closure   | Rubber Seal Contact  |  |   |                 |                |
| Ring Material   | 52100 Chrome Steel   |  |   |                 |                |
| Ball Material   | 52100 Chrome Steel   |  |   |                 |                |
| Brand   | FAG  |  |   |                 |                |
| Radial Clearance  | C3   |  |   |                 |                |
| Lubrication   | L069 Polycarbamide Ester Oil   |  |   |                 |                |
| Series  | 6308   |  | COMPONENT   | METRIC SERIES S | SEALED         |
| PIB   | Pacific International Bearing, Inc.<br>33258 Central Ave, Union City, CA 94587<br>1-800-228-8895, 510-512-7000,<br>info@pibsales.com<br>www.pibsales.com | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice. PIB<br>makes no representations, warranties or<br>guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for<br>any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications. | 6308–C–2HRS–L069–C3<br>FAG<br>40 Mm X 90 Mm X 23 Mm, Single Row |                 | UNIT<br>METRIC |
|   |  |  | Radial, Deep Groov<br>Contact Ru                                |                 | SHEET          |