T AI W A.N.			B rs rs D d	F	
Bore Diameter (d) 25 mm		Non-contact sealed type (LLB)			
Outside Diameter (D) 37 mm					
Width (B) 7 mm Classing Distance					
Closure Rubber Seal Non-Contact					
Ring Material 52100 Chrome Steel					
Ball Material	52100 Chrome Steel				
Brand	TPI				
Precision	Abec 1				
Radial Clearance	C3				
Lubrication	2AS Shell Alvania Grease S2				
Dynamic Load(Cr)	966.68 lbs	4			
Static Load(C0r)	663.19 lbs	4	COMPONENT		
Series	6805		COMPONENT	METRIC SERIES S	PEALED
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for	6805–LLB–C3/2AS TPI 25 Mm X 37 Mm X 7 Mm, Single Row Radial,		UNIT METRIC
	info@pibsales.com www.pibsales.com	accuracy, completeness, of suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	Deep Groove Ball Ball Bearing, Two Non- contact Rubber Seals		SHEET