|  |  | D   | $D_1$ d $D_1$ $D_$ | d <sub>1</sub>     |            |
|--|--|---|--|--------------------|------------|
| Bore Diameter (d)30 mmOutside Diameter (D)62 mm                                |  |   | _ B _  |                    |            |
| Width (B)  | 16 mm  |   |  |                    |            |
| Contact Angle  | 40° contact angle  | —   |  |                    |            |
| Bearing Arrangement Single - Universal Matched                                 |  |   |  |                    |            |
| Brand FAG  |  |   |  |                    |            |
| Ring Material Single - Universal Matched                                       |  |   |  |                    |            |
| Ball Material  | Chrome Steel 100Cr6  |   |  |                    |            |
| Dynamic Load(Cr)   | 5193.09 lbs  |   |  | [                  |            |
| Static Load(C0r)   | 3169.81 lbs  |   | COMPONENT  | Angular Contact Ba | ll Bearing |
| Pacific International Bearing, Inc.<br>33258 Central Ave, Union City, CA 94587 |  | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice. PIB<br>makes no representations, warranties or                       | 7206-B-XL-TVP-UO   |                    | UNIT       |
|  | 1-800-228-8895, 510-512-7000,<br>info@pibsales.com<br>www.pibsales.com | guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for<br>any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications. | 30mm X 62mm X 16mm, Angular Contac<br>Ball Bearing, Plastic Cage, Single -   |                    | METRIC     |
|  |  |   | Universa   | l Matched          | SHEET      |