

			D	$D_1$ d $\alpha$	d <sub>1</sub>		
		65 mm			1		I
		120 mm	<u>1</u>				1
		23 mm		B			I
		40° contact angle					I
nt		Single - Universal Matched					1
		FAG					1
		Single – Universal Matched					1
		Chrome Steel 100Cr6					
		15287.01 lbs					1
		11690.07 lbs		COMPONENT	Angular Contact Ba	ll Bearing	I
	Pacifi	ic International Bearing, Inc.	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB	7213-B-XL-MP-U0		UNIT	
33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com		Central Ave, Union City, CA 94587 00-228-8895, 510-512-7000, info@pibsales.com	makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	FA 65mm X 120mm X 23r Ball Bearing, Solid E	nm, Angular Contact	METRIC	
	www.pibsales.com			Universal Matched		SHEET	

Bore Diameter (d)	65 mm
Outside Diameter (D)	120 mm
Width (B)	23 mm
Contact Angle	40° contact angle
Bearing Arrangement	Single - Universal Matched
Brand	FAG
Ring Material	Single - Universal Matched
Ball Material	Chrome Steel 100Cr6
Dynamic Load(Cr)	15287.01 lbs
Static Load(C0r)	11690.07 lbs