



|                      |                            |
|----------------------|----------------------------|
| Bore Diameter (d)    | 100 mm                     |
| Outside Diameter (D) | 180 mm                     |
| Width (B)            | 34 mm                      |
| Contact Angle        | 40° contact angle          |
| Bearing Arrangement  | Single - Universal Matched |
| Brand                | FAG                        |
| Ring Material        | Single - Universal Matched |
| Ball Material        | Chrome Steel 100Cr6        |
| Dynamic Load(Cr)     | 31922.87 lbs               |
| Static Load(C0r)     | 27876.31 lbs               |

|           |                              |
|-----------|------------------------------|
| COMPONENT | Angular Contact Ball Bearing |
|-----------|------------------------------|



Pacific International Bearing, Inc.  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
 info@pibsales.com  
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

|   |        |
|---|--------|
| <b>7220-B-XL-MP-UA</b><br>FAG<br>100mm X 180mm X 34mm, Angular<br>Contact Ball Bearing, Solid Brass Cage,<br>Single - Universal Matched | UNIT   |
|   | METRIC |
|   | SHEET  |