

			D	D_1 d α	d ₁		
		240 mm			<u>I</u>		
)		440 mm					
		72 mm		B			
		40° contact angle					
nt		Single - Universal Matched					
		FAG					
		Single - Universal Matched					
		Chrome Steel 100Cr6					
		98915.93 lbs					
		159614.35 lbs		COMPONENT	Angular Contact Ba	ll Bearing	
Decific International Paaring Inc.		: International Bearing, Inc.	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	7248-B-MP-UA FAG 240mm X 440mm X 72mm, Angular Contact Ball Bearing, Solid Brass Cage, Single Universal Matched		UNIT	
	33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com					METRIC	
www.pibsales.com		www.pibsales.com				SHEET	

Bore Diameter (d)	240 mm
Outside Diameter (D)	440 mm
Width (B)	72 mm
Contact Angle	40° contact angle
Bearing Arrangement	Single - Universal Matched
Brand	FAG
Ring Material	Single - Universal Matched
Ball Material	Chrome Steel 100Cr6
Dynamic Load(Cr)	98915.93 lbs
Static Load(C0r)	159614.35 lbs