

			D	$D_1$ d $\alpha$	d <sub>1</sub>		
		40 mm			<u>I</u>		
		90 mm	<u>1</u>				
		23 mm		B			
		40° contact angle					
nt		Single - Universal Matched					
		FAG					
		Single – Universal Matched					
		Chrome Steel 100Cr6					
		12814.11 lbs					
		7755.91 lbs		COMPONENT	Angular Contact Ba	ll Bearing	
	Pacifi	fic International Bearing, Inc.	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB	7308-B-X	L-MP-UA	UNIT	
33258 Cent 1-800- i		entral Ave, Union City, CA 94587 0-228-8895, 510-512-7000, info@pibsales.com	makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or	FA 40mm X 90mm X 23n Ball Bearing, Solid E	nm, Angular Contact	METRIC	
		www.pibsales.com	specifications. You are solely responsible for the use of the file, information or specifications.	Universal Matched		SHEET	

Bore Diameter (d)	40 mm		
Outside Diameter (D)	90 mm		
Width (B)	23 mm		
Contact Angle	40° contact angle		
Bearing Arrangement	Single - Universal Matched		
Brand	FAG		
Ring Material	Single - Universal Matched		
Ball Material	Chrome Steel 100Cr6		
Dynamic Load(Cr)	12814.11 lbs		
Static Load(C0r)	7755.91 lbs		