| | | D | D_1 d C | | |
|---|--|--|-------------------|---|-------|
| Bore Diameter (d) 70 mm | | | B | | |
| Outside Diameter (D) | 150 mm | - | | | |
| Width (B) | 35 mm | - | | | |
| Contact Angle 40° contact angle | | - | | | |
| Bearing Arrangement Single - Universal Matched | | 4 | | | |
| Brand FAG | | 4 | | | |
| Ring Material | Single - Universal Matched | 4 | | | |
| Ball Material Chrome Steel 100Cr6 Dumomial and (Cr) 28235-82 km | | | | 1 | |
| Dynamic Load(Cr) Static Load(C0r) | 28325.93 lbs 20907.23 lbs | COMPONENT Angular Contact Ball Bearing | | ll Bearing | |
| PIB | Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com | This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications. | FA | L-TVP-UA | |
| | | | Ball Bearing, Pla | mm, Angular Contact stic Cage, Single - l Matched | SHEET |