|                         | B  |             | a<br>r <sub>1</sub><br>r <sub>1</sub><br>r<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f<br>f |   |  |        |
|-------------------------|--|-------------|--|---|--|--------|
| Bore Diameter (d) 17 mm |  | 17 mm       |  |   |  |        |
| Outside Diameter (D)    |  | 40 mm       |  |   |  |        |
| Width (B)               |  | 12 mm       |  |   |  |        |
| Dynamic Load AxialCA    |  | 3866.71 lbs |  |   |  |        |
| Static Load Axial ca    |  | 7306.29 lbs |  |   |  |        |
| Brand                   |  | FAG         |  | Axial Angular Contact   |  |        |
|                         |  |             | -  | COMPONENT Bearings  |  |        |
|                         | Pacific International Bearing, Inc.<br>33258 Central Ave, Union City, CA 94587<br>1-800-228-8895, 510-512-7000,<br>info@pibsales.com<br>www.pibsales.com |             |  | 7602017-TVPUNITFAGFAG17mm X 40mm X 12mm, Axial Angular<br>Contact, Ball Bearing, Single Direction, No<br>Screw MountingMetricStreetStreet |  | UNIT   |
| <b>ÝI</b> ₿             |  |             |  |   |  | Metric |
|                         |  |             |  |   |  | SHEET  |