



| | | | |
|-------------------------------|----------------------------------|---------------------------|-----------------------|
| O.D. (D): | 2.000 in (50.8 mm) | Static Torque: | 400 lb-in |
| Brand: | Ruland | Screw Material: | Alloy Steel |
| Dynamic Torque Reversing: | 100 lb-in | Bore Tolerance: | +0.001 in / -0.000 in |
| Shaft Tolerance: | +0.0000 in / -0.0005 in | Material: | Aluminum |
| Zero-Backlash?: | Yes | Bore (B1): | 1.0000 in |
| Balanced Design: | Yes | Bore (B2): | 0.8750 in |
| UNSPC: | 31163018 | Keyway: | No |
| Cap Screw: | M5 | B1 Max Shaft Penetration: | 1.099 in |
| Dynamic Torque Non-Reversing: | 200 lb-in | B2 Max Shaft Penetration: | 1.099 in |
| Hex Wrench Size: | 4.0 mm | Seating Torque: | 9.5 Nm |
| Maximum Speed: | 10000 RPM | Screw Finish: | Black Oxide |
| Torsional Stiffness: | 950 lb-in/Deg | Length (L): | 2.413 in (61.3 mm) |
| Angular Misalignment: | 2.0 deg | ISO 9001:2015: | Certified |
| Parallel Misalignment: | 0.010 in | REACH: | Compliant |
| Axial Motion: | 0.020 in | RoHS3: | Compliant |
| Bellows Attachment Method: | Epoxy | Conflict Minerals: | Compliant |
| Length Tolerance: | +/- 0.030 in | Tariff Code: | 8483.60.8000 |
| Temperature: | -40°F to 200°F (-40°C to 93°C) | Number of Screws: | 2 ea |
| Product Group: | Bellows Coupling Standard Length | Recommended Hex Key: | Metric Hex Keys |

| | |
|-----------|----------------------------------|
| COMPONENT | Bellows Coupling Standard Length |
|-----------|----------------------------------|



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

BC32-16-14-A
Ruland
1" X 7/8" Bores, 2.000" Od, 2.413" Length,
Bellows Coupling, High Stiffness,
Aluminum

UNIT

Inch

SHEET