



O.D. (D):	2.000 in (50.8 mm)	Static Torque:	400 lb-in (45.2 Nm)
Brand:	Ruland	Screw Material:	Alloy Steel
Dynamic Torque Reversing:	100 lb-in (11.30 Nm)	Bore Tolerance:	+0.001 in / -0.000 in (+0.03 mm / -0.00 mm)
Shaft Tolerance:	+0.0000 in / -0.0005 in +0.000 mm / -0.013 mm	Material:	Aluminum
Zero-Backlash?:	Yes	Bore (B1):	25 mm
Balanced Design:	Yes	Bore (B2):	0.5000 in
UNSPC:	31163018	Keyway:	No
Cap Screw:	M5	B1 Max Shaft Penetration:	1.099 in (27.9 mm)
Dynamic Torque Non-Reversing:	200 lb-in (22.60 Nm)	B2 Max Shaft Penetration:	1.099 in (27.9 mm)
Hex Wrench Size:	4.0 mm	Seating Torque:	9.5 Nm
Maximum Speed:	10000 RPM	Screw Finish:	Black Oxide
Torsional Stiffness:	950 lb-in/Deg (108 Nm/Deg)	Length (L):	2.413 in (61.3 mm)
Angular Misalignment:	2.0 deg	ISO 9001:2015:	Certified
Parallel Misalignment:	0.010 in (0.25 mm)	REACH:	Compliant
Axial Motion:	0.020 in (0.51 mm)	RoHS3:	Compliant
Bellows Attachment Method:	Epoxy	Conflict Minerals:	Compliant
Length Tolerance:	+/- 0.030 in (0.76 mm)	Tariff Code:	8483.60.8000
Temperature:	-40°F to 200°F (-40°C to 93°C)	Number of Screws:	2 ea
Product Group:	Bellows Coupling Standard Length	Recommended Hex Key:	Metric Hex Keys

COMPONENT	Bellows Coupling Standard Length
-----------	----------------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

BC32-25MM-1/2"-A
Ruland
25mm X 1/2" Bores, 2.000" (50.8mm), Od,
2.413" (61.3mm) Length, Bellows Coupling,
High Stiffness, Aluminum

UNIT
Inch/Metric
SHEET