



O.D. (D):	2.250 in (57.2 mm)	Static Torque:	530 lb-in (60.00 Nm)
Brand:	Ruland	Screw Material:	Alloy Steel
Dynamic Torque Reversing:	132 lb-in (15.00 Nm)	Bore Tolerance:	+0.001 in / -0.000 in (+0.03 mm / -0.00 mm)
Shaft Tolerance:	+0.0000 in / -0.0005 in +0.000 mm / -0.013 mm	Material:	Aluminum
Zero-Backlash?:	Yes	Bore (B1):	1.1250 in
Balanced Design:	Yes	Bore (B2):	20 mm
UNSPC:	31163018	Keyway:	No
Cap Screw:	M6	B1 Max Shaft Penetration:	1.496 in (38.0 mm)
Dynamic Torque Non-Reversing:	265 lb-in (30.00 Nm)	B2 Max Shaft Penetration:	1.496 in (38.0 mm)
Hex Wrench Size:	5.0 mm	Seating Torque:	16 Nm
Maximum Speed:	10000 RPM	Screw Finish:	Black Oxide
Torsional Stiffness:	1200 lb-in/Deg (135 Nm/Deg)	Length (L):	3.235 in (82.2 mm)
Angular Misalignment:	2.0 deg	ISO 9001:2015:	Certified
Parallel Misalignment:	0.012 in (0.30 mm)	REACH:	Compliant
Axial Motion:	0.030 in (0.76 mm)	RoHS3:	Compliant
Bellows Attachment Method:	Epoxy	Conflict Minerals:	Compliant
Length Tolerance:	+/- 0.030 in (0.76 mm)	Tariff Code:	8483.60.8000
Temperature:	-40°F to 200°F (-40°C to 93°C)	Number of Screws:	2 ea
Product Group:	Bellows Coupling Standard Length	Recommended Hex Key:	Metric Hex Keys

COMPONENT	Bellows Coupling Standard Length
------------------	---



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

BC36-1 1/8"-20MM-A
Ruland
1 1/8" X 20mm Bores, 2.250" Od, 3.235"
Length, Bellows Coupling, High Stiffness,
Aluminum

UNIT
Inch/Metric
SHEET