



|                               |                                                  |                           |                                                |
|-------------------------------|--------------------------------------------------|---------------------------|------------------------------------------------|
| O.D. (D):                     | 2.750 in (69.9 mm)                               | Maximum Speed:            | 10000 RPM                                      |
| Brand:                        | Ruland                                           | Length (L):               | 3.431 in (87.1 mm)                             |
| Dynamic Torque Reversing:     | 231.3 lb-in (26.13 Nm)                           | Bore Tolerance:           | +0.001 in / -0.000 in<br>(+0.03 mm / -0.00 mm) |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in<br>+0.000 mm / -0.013 mm | Material:                 | Aluminum                                       |
| Zero-Backlash?:               | Yes                                              | Bore (B1):                | 32 mm                                          |
| Balanced Design:              | Yes                                              | Bore (B2):                | 1.2500 in                                      |
| UNSPC:                        | 31163018                                         | Keyway:                   | No                                             |
| Cap Screw:                    | M8                                               | B1 Max Shaft Penetration: | 1.582 in (40.2 mm)                             |
| Static Torque:                | 925 lb-in (104.5 Nm)                             | B2 Max Shaft Penetration: | 1.582 in (40.2 mm)                             |
| Dynamic Torque Non-Reversing: | 462.5 lb-in (52.25 Nm)                           | Screw Material:           | Alloy Steel                                    |
| Torsional Stiffness:          | 2100 lb-in/Deg (237 Nm/Deg)                      | Hex Wrench Size:          | 6.0 mm                                         |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)                   | Screw Finish:             | Black Oxide                                    |
| Angular Misalignment:         | 2.0 deg                                          | ISO 9001:2015:            | Certified                                      |
| Parallel Misalignment:        | 0.012 in (0.30 mm)                               | REACH:                    | Compliant                                      |
| Axial Motion:                 | 0.030 in (0.76 mm)                               | RoHS3:                    | Compliant                                      |
| Bellows Attachment Method:    | Epoxy                                            | Conflict Minerals:        | Compliant                                      |
| Length Tolerance:             | +/- 0.030 in (0.76 mm)                           | Tariff Code:              | 8483.60.8000                                   |
| Recommended Hex Key:          | Metric Hex Keys                                  | Number of Screws:         | 2 ea                                           |
| B1 Min Shaft Penetration:     | 0.750 in (19.1 mm)                               | Seating Torque:           | 39 Nm                                          |
| Product Group:                | Bellows Coupling Standard Length                 | B2 Min Shaft Penetration: | 0.750 in (19.1 mm)                             |

COMPONENT

Bellows Coupling  
Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

BC44-32MM-1 1/4"-A  
Ruland

|             |
|-------------|
| UNIT        |
| Inch/Metric |
| SHEET       |