



|                               |                                                  |                           |                                                |
|-------------------------------|--------------------------------------------------|---------------------------|------------------------------------------------|
| O.D. (D):                     | 1.313 in (33.3 mm)                               | Static Torque:            | 120 lb-in (13.6 Nm)                            |
| Brand:                        | Ruland                                           | Number of Screws:         | 2 ea                                           |
| Seating Torque:               | 2.1 Nm                                           | Screw Finish:             | Black Oxide                                    |
| Zero-Backlash?:               | Yes                                              | Bore (B2):                | 11 mm                                          |
| Balanced Design:              | Yes                                              | Keyway:                   | Yes                                            |
| UNSPC:                        | 31163018                                         | Keyway (K1):              | 3/16 in                                        |
| Cap Screw:                    | M3                                               | Keyway (K2):              | 4 mm                                           |
| Hex Wrench Size:              | 2.5 mm                                           | B2 Max Shaft Penetration: | 0.804 in (20.4 mm)                             |
| Dynamic Torque Non-Reversing: | 60 lb-in (6.80 Nm)                               | B1 Max Shaft Penetration: | 0.804 in (20.4 mm)                             |
| Dynamic Torque Reversing:     | 30 lb-in (3.40 Nm)                               | Bore Tolerance:           | +0.001 in / -0.000 in<br>(+0.03 mm / -0.00 mm) |
| Angular Misalignment:         | 1.5 deg                                          | Screw Material:           | Alloy Steel                                    |
| Torsional Stiffness:          | 400 lb-in/Deg (45 Nm/Deg)                        | Length (L):               | 1.700 in (43.2 mm)                             |
| Parallel Misalignment:        | 0.006 in (0.15 mm)                               | ISO 9001:2015:            | Certified                                      |
| Axial Motion:                 | 0.016 in (0.40 mm)                               | REACH:                    | Compliant                                      |
| Bellows Attachment Method:    | Epoxy                                            | RoHS3:                    | Compliant                                      |
| Length Tolerance:             | +/- 0.030 in (0.76 mm)                           | Conflict Minerals:        | Compliant                                      |
| Maximum Speed:                | 10000 RPM                                        | Tariff Code:              | 8483.60.8000                                   |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)                   | Material:                 | Aluminum                                       |
| Product Group:                | Bellows Coupling Standard Length                 | Bore (B1):                | 0.6250 in                                      |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in<br>+0.000 mm / -0.013 mm | Recommended Hex Key:      | Metric Hex Keys                                |

COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BCK21-5/8"-11MM-A**  
**Ruland**  
5/8" X 11mm Bores, 1.313" (33.3mm), Od,  
1.700" (43.2mm) Length, Bellows Coupling  
With Keyways, High Stiffness, Aluminum

|             |
|-------------|
| UNIT        |
| Inch/Metric |
| SHEET       |