



O.D. (D):	1.313 in (33.3 mm)	Static Torque:	120 lb-in (13.6 Nm)
Brand:	Ruland	Number of Screws:	2 ea
Seating Torque:	2.1 Nm	Screw Finish:	Black Oxide
Zero-Backlash?:	Yes	Bore (B2):	13 mm
Balanced Design:	Yes	Keyway:	Yes
UNSPC:	31163018	Keyway (K1):	3/16 in
Cap Screw:	M3	Keyway (K2):	5 mm
Hex Wrench Size:	2.5 mm	B2 Max Shaft Penetration:	0.804 in (20.4 mm)
Dynamic Torque Non-Reversing:	60 lb-in (6.80 Nm)	B1 Max Shaft Penetration:	0.804 in (20.4 mm)
Dynamic Torque Reversing:	30 lb-in (3.40 Nm)	Bore Tolerance:	+0.001 in / -0.000 in (+0.03 mm / -0.00 mm)
Angular Misalignment:	1.5 deg	Screw Material:	Alloy Steel
Torsional Stiffness:	400 lb-in/Deg (45 Nm/Deg)	Length (L):	1.700 in (43.2 mm)
Parallel Misalignment:	0.006 in (0.15 mm)	ISO 9001:2015:	Certified
Axial Motion:	0.016 in (0.40 mm)	REACH:	Compliant
Bellows Attachment Method:	Epoxy	RoHS3:	Compliant
Length Tolerance:	+/- 0.030 in (0.76 mm)	Conflict Minerals:	Compliant
Maximum Speed:	10000 RPM	Tariff Code:	8483.60.8000
Temperature:	-40°F to 200°F (-40°C to 93°C)	Material:	Aluminum
Product Group:	Bellows Coupling Standard Length	Bore (B1):	0.6250 in
Shaft Tolerance:	+0.0000 in / -0.0005 in +0.000 mm / -0.013 mm	Recommended Hex Key:	Metric Hex Keys

COMPONENT	Bellows Coupling Standard Length
-----------	----------------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

BCK21-5/8"-13MM-A
Ruland
5/8" X 13mm Bores, 1.313" (33.3mm), Od,
1.700" (43.2mm) Length, Bellows Coupling
With Keyways, High Stiffness, Aluminum

UNIT
Inch/Metric
SHEET