



O.D. (D):	1.625 in (41.3 mm)	Seating Torque:	4.6 Nm
Brand:	Ruland	Length (L):	2.035 in (51.7 mm)
Static Torque:	250 lb-in (28.0 Nm)	Screw Material:	Alloy Steel
Shaft Tolerance:	+0.0000 in / -0.0005 in +0.000 mm / -0.013 mm	Bore (B1):	0.6250 in
Zero-Backlash?:	Yes	Bore (B2):	13 mm
Balanced Design:	Yes	Keyway:	Yes
UNSPC:	31163018	Keyway (K1):	3/16 in
Cap Screw:	M4	Keyway (K2):	5 mm
Hex Wrench Size:	3.0 mm	B2 Max Shaft Penetration:	0.946 in (24.0 mm)
Dynamic Torque Non-Reversing:	125 lb-in (14.00 Nm)	B1 Max Shaft Penetration:	0.946 in (24.0 mm)
Torsional Stiffness:	550 lb-in/Deg (63 Nm/Deg)	Bore Tolerance:	+0.001 in / -0.000 in (+0.03 mm / -0.00 mm)
Dynamic Torque Reversing:	62.5 lb-in (7.00 Nm)	Number of Screws:	2 ea
Angular Misalignment:	2.0 deg	Screw Finish:	Black Oxide
Parallel Misalignment:	0.010 in (0.25 mm)	ISO 9001:2015:	Certified
Axial Motion:	0.020 in (0.51 mm)	REACH:	Compliant
Bellows Attachment Method:	Epoxy	RoHS3:	Compliant
Length Tolerance:	+/- 0.030 in (0.76 mm)	Conflict Minerals:	Compliant
Maximum Speed:	10000 RPM	Tariff Code:	8483.60.8000
Temperature:	-40°F to 200°F (-40°C to 93°C)	Material:	Aluminum
Product Group:	Bellows Coupling Standard Length	Recommended Hex Key:	Metric Hex Keys

COMPONENT	Bellows Coupling Standard Length
-----------	----------------------------------



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BCK26-5/8"-13MM-A**  
**Ruland**  
5/8" X 13mm Bores, 1.625" (41.3mm), Od,  
2.035" (51.7mm) Length, Bellows Coupling  
With Keyways, High Stiffness, Aluminum

UNIT
Inch/Metric
SHEET