



|                               |                                  |                           |                       |
|-------------------------------|----------------------------------|---------------------------|-----------------------|
| O.D. (D):                     | 2.250 in (57.2 mm)               | Seating Torque:           | 16 Nm                 |
| Brand:                        | Ruland                           | Length (L):               | 3.235 in (82.2 mm)    |
| Static Torque:                | 530 lb-in                        | Screw Material:           | Alloy Steel           |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in          | Bore (B1):                | 1.1250 in             |
| Zero-Backlash?:               | Yes                              | Bore (B2):                | 0.6250 in             |
| Balanced Design:              | Yes                              | Keyway:                   | Yes                   |
| UNSPC:                        | 31163018                         | Keyway (K1):              | 1/4 in                |
| Cap Screw:                    | M6                               | Keyway (K2):              | 3/16 in               |
| Hex Wrench Size:              | 5.0 mm                           | B2 Max Shaft Penetration: | 1.496 in              |
| Dynamic Torque Non-Reversing: | 265 lb-in                        | B1 Max Shaft Penetration: | 1.496 in              |
| Torsional Stiffness:          | 1200 lb-in/Deg                   | Bore Tolerance:           | +0.004 in / +0.001 in |
| Dynamic Torque Reversing:     | 132 lb-in                        | Number of Screws:         | 2 ea                  |
| Angular Misalignment:         | 2.0 deg                          | Screw Finish:             | Black Oxide           |
| Parallel Misalignment:        | 0.012 in                         | ISO 9001:2015:            | Certified             |
| Axial Motion:                 | 0.030 in                         | REACH:                    | Compliant             |
| Bellows Attachment Method:    | Epoxy                            | RoHS3:                    | Compliant             |
| Length Tolerance:             | +/- 0.030 in                     | Conflict Minerals:        | Compliant             |
| Maximum Speed:                | 10000 RPM                        | Tariff Code:              | 8483.60.8000          |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)   | Material:                 | Aluminum              |
| Product Group:                | Bellows Coupling Standard Length | Recommended Hex Key:      | Metric Hex Keys       |

COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BCK36-18-10-A**  
**Ruland**  
11/8" X 5/8" Bores, 2.250" Od, 3.235"  
Length, Bellows Coupling With Keyways,  
High Stiffness, Aluminum

UNIT

Inch

SHEET