



| | | | |
|-------------------------------|--|---------------------------|--|
| O.D. (D): | 1.625 in (41.3 mm) | Seating Torque: | 4.6 Nm |
| Brand: | Ruland | Bore Tolerance: | +0.001 in / -0.000 in (+0.03 mm / -0.00 mm) |
| Hex Wrench Size: | 3.0 mm | Number of Screws: | 2 ea |
| Temperature: | -40°F to 200°F (-40°C to 93°C) | Material: | Aluminum |
| Product Group: | Bellows Coupling Standard Length | Bore (B1): | 20 mm |
| Shaft Tolerance: | +0.0000 in / -0.0005 in +0.000 mm / -0.013 mm | Bore (B2): | 0.6250 in |
| Zero-Backlash?: | Yes | Keyway: | No |
| Balanced Design: | Yes | B1 Max Shaft Penetration: | 0.946 in (24.0 mm) |
| UNSPC: | 31163018 | Length (L): | 2.316 in (58.8 mm) |
| Maximum Speed: | 10000 RPM | B2 Max Shaft Penetration: | 0.946 in (24.0 mm) |
| Cap Screw: | M4 | Screw Material: | Alloy Steel |
| Dynamic Torque Non-Reversing: | 125 lb-in (14.00 Nm) | Screw Finish: | Black Oxide |
| Dynamic Torque Reversing: | 62.5 lb-in (7.00 Nm) | ISO 9001:2015: | Certified |
| Torsional Stiffness: | 350 lb-in/Deg (39.4 Nm/Deg) | REACH: | Compliant |
| Angular Misalignment: | 3.0 deg | RoHS3: | Compliant |
| Parallel Misalignment: | 0.015 in (0.38 mm) | Conflict Minerals: | Compliant |
| Axial Motion: | 0.030 in (0.76 mm) | Tariff Code: | 8483.60.8000 |
| Bellows Attachment Method: | Epoxy | Length Tolerance: | +/- 0.030 in (0.76 mm) |
| Static Torque: | 250 lb-in (28.0 Nm) | | |

| | |
|-----------|----------------------------------|
| COMPONENT | Bellows Coupling Standard Length |
|-----------|----------------------------------|



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

BCL26-20MM-5/8"-A
Ruland
20mm X 5/8" Bores, 1.625" (41.3mm), Od,
2.316" (58.8 Mm) Length, Bellows
Coupling, Increased Misalignment,
Aluminum

| |
|-------------|
| UNIT |
| Inch/Metric |
| SHEET |