



|                                   |                                                  |                              |                                                |
|-----------------------------------|--------------------------------------------------|------------------------------|------------------------------------------------|
| O.D. (D):                         | 1.000 in (25.4 mm)                               | Static Torque:               | 60 lb-in (6.8 Nm)                              |
| Brand:                            | Ruland                                           | Number of Screws:            | 2 ea                                           |
| Seating Torque:                   | 2.1 Nm                                           | Bore Tolerance:              | +0.001 in / -0.000 in<br>(+0.03 mm / -0.00 mm) |
| Product Group:                    | Bellows Coupling -<br>Extended Length            | Material:                    | Aluminum                                       |
| Shaft Tolerance:                  | +0.0000 in / -0.0005 in<br>+0.000 mm / -0.013 mm | Bore (B1):                   | 0.5000 in                                      |
| Zero-Backlash?:                   | Yes                                              | Bore (B2):                   | 6 mm                                           |
| Balanced Design:                  | Yes                                              | Keyway:                      | Yes                                            |
| UNSPC:                            | 31163018                                         | Keyway (K1):                 | 1/8 in                                         |
| Cap Screw:                        | M3                                               | Keyway (K2):                 | NK                                             |
| Hex Wrench Size:                  | 2.5 mm                                           | B2 Max Shaft<br>Penetration: | 0.715 in (18.2 mm)                             |
| Dynamic Torque<br>Reversing:      | 15 lb-in (1.70 Nm)                               | B1 Max Shaft<br>Penetration: | 0.715 in (18.2 mm)                             |
| Dynamic Torque Non-<br>Reversing: | 30 lb-in (3.40 Nm)                               | Length (L):                  | 1.523 in (38.7 mm)                             |
| Torsional Stiffness:              | 185 lb-in/Deg (20.9<br>Nm/Deg)                   | Screw Material:              | Alloy Steel                                    |
| Angular Misalignment:             | 3.0 deg                                          | Screw Finish:                | Black Oxide                                    |
| Parallel Misalignment:            | 0.008 in (0.20 mm)                               | ISO 9001:2015:               | Certified                                      |
| Axial Motion:                     | 0.024 in (0.61 mm)                               | REACH:                       | Compliant                                      |
| Bellows Attachment<br>Method:     | Epoxy                                            | RoHS3:                       | Compliant                                      |
| Length Tolerance:                 | +/- 0.030 in (0.76 mm)                           | Conflict Minerals:           | Compliant                                      |
| Maximum Speed:                    | 10000 RPM                                        | Tariff Code:                 | 8483.60.8000                                   |
| Temperature:                      | -40°F to 200°F (-40°C to<br>93°C)                | Recommended Hex<br>Key:      | Metric Hex Keys                                |

COMPONENT

Bellows Coupling - Extended  
Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BCLK16-1/2"-6MM-A**  
**Ruland**  
1/2" X 6mm Bellows Coupling With  
Keyways Bores, 1.000" (25.4mm) Od.,  
1.523" (38.7mm) Length, Bellows Coupling  
With Keyways, Increased Misalignment,  
Aluminum

|             |
|-------------|
| UNIT        |
| Inch/Metric |
| SHEET       |