



O.D. (D):	1.625 in (41.3 mm)	Number of Screws:	2 ea
Brand:	Ruland	B2 Max Shaft Penetration:	0.946 in
Seating Torque:	4.6 Nm	Tariff Code:	8483.60.8000
Maximum Speed:	10000 RPM	Material:	Aluminum
Temperature:	-40°F to 200°F (-40°C to 93°C)	Bore (B1):	0.5000 in
Product Group:	Bellows Coupling Standard Length	Bore (B2):	0.5000 in
Shaft Tolerance:	+0.0000 in / -0.0005 in	Keyway:	Yes
Zero-Backlash?:	Yes	Keyway (K1):	1/8 in
Balanced Design:	Yes	Keyway (K2):	1/8 in
UNSPC:	31163018	Length (L):	2.316 in (58.8 mm)
Hex Wrench Size:	3.0 mm	B1 Max Shaft Penetration:	0.946 in
Cap Screw:	M4	Bore Tolerance:	+0.001 in / -0.000 in
Dynamic Torque Non-Reversing:	125 lb-in	Screw Material:	Alloy Steel
Dynamic Torque Reversing:	62.5 lb-in	Screw Finish:	Black Oxide
Torsional Stiffness:	350 lb-in/Deg	ISO 9001:2015:	Certified
Angular Misalignment:	3.0 deg	REACH:	Compliant
Parallel Misalignment:	0.015 in	RoHS3:	Compliant
Axial Motion:	0.030 in	Conflict Minerals:	Compliant
Bellows Attachment Method:	Epoxy	Length Tolerance:	+/- 0.030 in
Static Torque:	250 lb-in		

COMPONENT	Bellows Coupling Standard Length
-----------	----------------------------------



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BCLK26-8-8-A**  
**Ruland**  
1/2" X 1/2" Bores, 1.625", Od, 2.316" Length,  
Bellows Coupling With Keyways,  
Increased Misalignment, Aluminum

UNIT

Inch

SHEET