



O.D. (D):	2 7/8 in	Number of Screws:	1 ea
Brand:	Ruland	Screw Location (R):	1.188 in
Material:	316 Stainless Steel	Seating Torque:	190 lb-in
Bore (B1):	1.8750 in	Hex Wrench Size:	1/4 in
Bore Tolerance:	+0.0020 in / +0.0005 in	Temperature:	-40°F to 350°F (-40°C to 176°C)
Screw Material:	316 Stainless Steel	Country of Origin:	USA
Screw Finish:	Bright	Finish Specification:	Bright No Plating
Forged Clamp Screw:	5/16-24	Shaft Tolerance:	+0.0000 in / -0.0005 in
ISO 9001:2015:	Certified	UNSPC:	3162811
REACH:	Compliant	Clearance Diameter (C) MAX:	3.160 in
RoHS3:	Compliant	Material Specification:	316 Stainless Steel
Conflict Minerals:	Compliant	Width (W):	0.688 in
Tariff Code:	8483.60.8000		



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

COMPONENT	Shaft Collar - One-Piece
CL-30-ST Ruland 1.8750in Bore; 2.8750in Od, 0.6880in Width, One-piece Shaft Collar, 316 Stainless Steel, Clamp Style	UNIT
	Inch
	SHEET