



| | | | |
|---------------------|-------------------------|-----------------------------|---------------------------------|
| O.D. (D): | 3 1/8 in | Number of Screws: | 1 ea |
| Brand: | Ruland | Screw Location (R): | 1.297 in |
| Material: | Black Oxide Steel | Seating Torque: | 325 lb-in |
| Bore (B1): | 2.0625 in | Hex Wrench Size: | 1/4 in |
| Bore Tolerance: | +0.0020 in / +0.0005 in | Temperature: | -40°F to 350°F (-40°C to 176°C) |
| Screw Material: | Alloy Steel | Country of Origin: | USA |
| Screw Finish: | Black Oxide | Finish Specification: | Black Oxide |
| Forged Clamp Screw: | 5/16-24 | Shaft Tolerance: | +0.0000 in / -0.0005 in |
| ISO 9001:2015: | Certified | UNSPC: | 31162811 |
| REACH: | Compliant | Clearance Diameter (C) MAX: | 3.360 in |
| RoHS3: | Compliant | Material Specification: | 1215 Bar |
| Conflict Minerals: | Compliant | Width (W): | 0.750 in |
| Tariff Code: | 8483.60.8000 | | |

| | |
|-----------|--------------------------|
| COMPONENT | Shaft Collar - One-Piece |
|-----------|--------------------------|



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

| | |
|---|-------|
| CL-33-F Ruland 2.0625in Bore; 3.1250in Od, 0.7500in Width, One-piece Shaft Collar, Black Oxide Steel, Clamp Style | UNIT |
| | Inch |
| | SHEET |