



O.D. (D):	3 1/8 in	Number of Screws:	1 ea
Brand:	Ruland	Screw Location (R):	1.297 in
Material:	303 Stainless Steel	Seating Torque:	190 lb-in
Bore (B1):	2.0625 in	Hex Wrench Size:	1/4 in
Bore Tolerance:	+0.0020 in / +0.0005 in	Temperature:	-40°F to 350°F (-40°C to 176°C)
Screw Material:	18-8 300 Series Stainless Steel	Country of Origin:	USA
Screw Finish:	Bright	Finish Specification:	Bright No Plating
Forged Clamp Screw:	5/16-24	Shaft Tolerance:	+0.0000 in / -0.0005 in
ISO 9001:2015:	Certified	UNSPC:	31162811
REACH:	Compliant	Clearance Diameter (C) MAX:	3.360 in
RoHS3:	Compliant	Material Specification:	303 Stainless Steel
Conflict Minerals:	Compliant	Width (W):	0.750 in
Tariff Code:	8483.60.8000		

COMPONENT

Shaft Collar - One-Piece



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

CL-33-SS

Ruland

**2.0625in Bore; 3.1250in Od, 0.7500in Width,
 One-piece Shaft Collar, 303 Stainless
 Steel, Clamp Style**

UNIT

Inch

SHEET