



O.D. (D):	3 1/2 in	Number of Screws:	1 ea
Brand:	Ruland	Screw Location (R):	1.484 in
Material:	Aluminum	Seating Torque:	325 lb-in
Bore (B1):	2.4375 in	Hex Wrench Size:	1/4 in
Bore Tolerance:	+0.0020 in / +0.0005 in	Temperature:	-40°F to 225°F (-40°C to 107°C)
Screw Material:	Alloy Steel	Country of Origin:	USA
Screw Finish:	Black Oxide	Finish Specification:	Bright No Plating
Forged Clamp Screw:	5/16-24	Shaft Tolerance:	+0.0000 in / -0.0005 in
ISO 9001:2015:	Certified	UNSPC:	3162811
REACH:	Compliant	Clearance Diameter (C) MAX:	3.707 in
RoHS3:	Compliant	Material Specification:	2024-T351 Bar
Conflict Minerals:	Compliant	Width (W):	0.750 in
Tariff Code:	8483.60.8000		

COMPONENT

Shaft Collar - One-Piece



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

CL-39-A
Ruland
2.4375in Bore; 3.5000in Od, 0.7500in
Width, One-piece Shaft Collar, Aluminum,
Clamp Style

UNIT

Inch

SHEET