


O.D. (D):	13/4 in	Tariff Code:	8483.60.8000
Screw Location (R):	0.678 in	Conflict Minerals:	Compliant
Material Specification:	1215 Bar	RoHS3:	Compliant
Clearance Diameter (C) MAX:	2.032 in	REACH:	Compliant
UNSPC:	31162811	ISO 9001:2015:	Certified
Shaft Tolerance:	+0.0000 in / -0.0005 in	Forged Clamp Screw:	1/4/28
Finish Specification:	Black Oxide	Screw Finish:	Black Oxide
Country of Origin:	USA	Screw Material:	Alloy Steel
Temperature:	-40°F to 350°F (-40°C to 176°C)	Bore Tolerance:	+0.0020 in / +0.0005 in
Hex Wrench Size:	3/16 in	Bore (B1):	1.0000 in
Seating Torque:	170 lb-in	Brand:	Ruland
Number of Screws:	1ea	Width (W):	0.500 in
Material:	Black Oxide Steel		



COMPONENT

Shaft Collar - D-Bore



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

CLD-16-F

1in Bore; 1.7500in Od, 0.5000in Width, Dbore Shaft Collar, Black Oxide Steel, Onepiece, Clamp Style UNIT

Inch

SHEET