


0.D. (D)	7/8 in		
Tariff Code	8483.60.8000		
Bore (B1)	0.3750 in		
Bore Tolerance	+0.0020 in / +0.0005 in		
Screw Material	Alloy Steel		
Screw Finish	Black Oxide		
Forged Clamp Screw	#6-32		
ISO 9001:2015	Certified		
REACH	Compliant		
RoHS3	Compliant		
Conflict Minerals	Compliant		
Material	Aluminum		
Screw Location (R)	0.313 in		
Number of Screws	1ea		
Seating Torque	28 lb-in		
Hex Wrench Size	7/64 in		
Temperature	-40°F to 225°F (-40°C to 107°C)		
Country of Origin	USA		
Finish Specification	Bright No Plating		
Shaft Tolerance	+0.0000 in / -0.0005 in		
UNSPC	31162811		
Clearance Diameter (C) MAX	1.027 in		
Material Specification	2024-T351 Bar		
Brand	Ruland		



COMPONENT Shaft Collar - D-Bore



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

CLD-6-A

Ruland

.3750in Bore; .8750in Od, 0.343" Width, Dbore Shaft Collar, Aluminum, One-piece, Clamp Style

UNIT

Inch

SHEET