



O.D. (D):	11/8 in	Material:	Aluminum
Brand:	Ruland	Tariff Code:	8483.60.8000
Screw Location (R):	0.406 in	Conflict Minerals:	Compliant
Material Specification:	2024-T351 Bar	RoHS3:	Compliant
Clearance Diameter (C) MAX:	1.281 in	REACH:	Compliant
UNSPC:	31162811	ISO 9001:2015:	Certified
Shaft Tolerance:	+0.0000 in / -0.0005 in	Forged Clamp Screw:	#8-32
Finish Specification:	Bright No Plating	Screw Finish:	Black Oxide
Country of Origin:	USA	Screw Material:	Alloy Steel
Temperature:	-40°F to 225°F (-40°C to 107°C)	Bore Tolerance:	+0.0020 in / +0.0005 in
Hex Wrench Size:	9/64 in	Bore (B1):	0.5000 in
Seating Torque:	49 lb-in	Width (W):	0.406 in
Number of Screws:	1 ea		

COMPONENT	Shaft Collar - D-Bore
<b>CLD-8-A</b> <b>Ruland</b> .5000in Bore; 1.1250in Od, 0.406" Width, D-bore Shaft Collar, Aluminum, One-piece, Clamp Style	UNIT
	Inch
	SHEET



**Pacific International Bearing, Inc.**  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
[info@pibsales.com](mailto:info@pibsales.com)  
[www.pibsales.com](http://www.pibsales.com)

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.