



|                               |                                                  |                           |                                                |
|-------------------------------|--------------------------------------------------|---------------------------|------------------------------------------------|
| O.D. (D):                     | 1.625 in (41.3 mm)                               | Hex Wrench Size:          | 3.0 mm                                         |
| Brand:                        | Ruland                                           | Number of Screws:         | 2 ea                                           |
| Note:                         | Stainless steel hubs are available upon request. | Length (L):               | 2.165 in (55.0 mm)                             |
| Static Torque:                | 180 lb-in (20.3 Nm)                              | B2 Max Shaft Penetration: | 1.029 in (26.1 mm)                             |
| Maximum Speed:                | 10000 RPM                                        | Material:                 | Aluminum                                       |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)                   | Bore (B1):                | 18 mm                                          |
| Country of Origin:            | USA                                              | Bore (B2):                | 0.6250 in                                      |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in<br>+0.000 mm / -0.013 mm | Keyway:                   | No                                             |
| Balanced Design:              | Yes                                              | B1 Max Shaft Penetration: | 1.029 in (26.1 mm)                             |
| UNSPC:                        | 31163008                                         | Bore Tolerance:           | +0.001 in / -0.000 in<br>(+0.03 mm / -0.00 mm) |
| Dynamic Torque Non-Reversing: | 90 lb-in (10.15 Nm)                              | Tariff Code:              | 8483.60.8000                                   |
| Seating Torque:               | 4.6 Nm                                           | Screw Material:           | Alloy Steel                                    |
| Dynamic Torque Reversing:     | 45 lb-in (5.08 Nm)                               | Screw Finish:             | Black Oxide                                    |
| Torsional Stiffness:          | 375 lb-in/Deg (42.4 Nm/Deg)                      | Forged Clamp Screw:       | M4                                             |
| Angular Misalignment:         | 2.0 deg                                          | ISO 9001:2015:            | Certified                                      |
| Parallel Misalignment:        | 0.010 in (0.25 mm)                               | REACH:                    | Compliant                                      |
| Axial Motion:                 | 0.020 in (0.51 mm)                               | RoHS3:                    | Compliant                                      |
| Recommended Hex Key:          | Metric Hex Keys                                  | Conflict Minerals:        | Compliant                                      |
| B1 Min Shaft Penetration:     | 0.433 in (11.0 mm)                               | B2 Min Shaft Penetration: | 0.433 in (11.0 mm)                             |

COMPONENT

Disc Coupling - Double



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**DCD26-18MM-5/8"-A**  
**Ruland**  
18mm X 0.6250" Bores, 1.625" (41.3mm) Od,  
And 2.165" (55.0mm) Length, Clamp  
Double Disc Coupling, Accommodates All  
Types Of Misalignment, Anodized  
Aluminum Hubs, Stainless Steel Disc  
Springs, And A Center Spacer

|             |
|-------------|
| UNIT        |
| Inch/Metric |
| SHEET       |