



| | | | |
|-------------------------------|--|---------------------------|--|
| O.D. (D): | 2.000 in (50.8 mm) | Hex Wrench Size: | 4.0 mm |
| Brand: | Ruland | Number of Screws: | 2 ea |
| Note: | Stainless steel hubs are available upon request. | Length (L): | 2.519 in (64.0 mm) |
| Static Torque: | 350 lb-in (39.6 Nm) | B2 Max Shaft Penetration: | 1.192 in (30.3 mm) |
| Maximum Speed: | 10000 RPM | Material: | Aluminum |
| Temperature: | -40°F to 200°F (-40°C to 93°C) | Bore (B1): | 0.8750 in |
| Country of Origin: | USA | Bore (B2): | 14 mm |
| Shaft Tolerance: | +0.0000 in / -0.0005 in +0.000 mm / -0.013 mm | Keyway: | No |
| Balanced Design: | Yes | B1 Max Shaft Penetration: | 1.192 in (30.3 mm) |
| UNSPC: | 31163008 | Bore Tolerance: | +0.001 in / -0.000 in (+0.03 mm / -0.00 mm) |
| Dynamic Torque Non-Reversing: | 175 lb-in (19.80 Nm) | Tariff Code: | 8483.60.8000 |
| Seating Torque: | 9.5 Nm | Screw Material: | Alloy Steel |
| Dynamic Torque Reversing: | 87.5 lb-in (9.90 Nm) | Screw Finish: | Black Oxide |
| Torsional Stiffness: | 595 lb-in/Deg (67.2 Nm/Deg) | Forged Clamp Screw: | M5 |
| Angular Misalignment: | 2.0 deg | ISO 9001:2015: | Certified |
| Parallel Misalignment: | 0.012 in (0.30 mm) | REACH: | Compliant |
| Axial Motion: | 0.025 in (0.64 mm) | RoHS3: | Compliant |
| Recommended Hex Key: | Metric Hex Keys | Conflict Minerals: | Compliant |
| B1 Min Shaft Penetration: | 0.500 in (12.7 mm) | B2 Min Shaft Penetration: | 0.500 in (12.7 mm) |

COMPONENT

Disc Coupling - Double



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DCD32-7/8"-14MM-A
Ruland
0.8750" X 14mm Bores, 2.000" (50.8mm)
Od, And 2.519" (64.0mm) Length, Clamp
Double Disc Coupling, Accommodates All
Types Of Misalignment, Anodized
Aluminum Hubs, Stainless Steel Disc
Springs, And A Center Spacer

| |
|-------------|
| UNIT |
| Inch/Metric |
| SHEET |