



|                               |                                                  |                           |                                                |
|-------------------------------|--------------------------------------------------|---------------------------|------------------------------------------------|
| O.D. (D):                     | 2.250 in (57.2 mm)                               | Hex Wrench Size:          | 5.0 mm                                         |
| Brand:                        | Ruland                                           | Number of Screws:         | 2 ea                                           |
| Note:                         | Stainless steel hubs are available upon request. | Length (L):               | 3.080 in (78.2 mm)                             |
| Static Torque:                | 450 lb-in (50.9 Nm)                              | B2 Max Shaft Penetration: | 1.458 in (37.0 mm)                             |
| Maximum Speed:                | 10000 RPM                                        | Material:                 | Aluminum                                       |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)                   | Bore (B1):                | 0.8750 in                                      |
| Country of Origin:            | USA                                              | Bore (B2):                | 15 mm                                          |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in<br>+0.000 mm / -0.013 mm | Keyway:                   | No                                             |
| Balanced Design:              | Yes                                              | B1 Max Shaft Penetration: | 1.458 in (37.0 mm)                             |
| UNSPC:                        | 31163008                                         | Bore Tolerance:           | +0.001 in / -0.000 in<br>(+0.03 mm / -0.00 mm) |
| Dynamic Torque Non-Reversing: | 225 lb-in (25.45 Nm)                             | Tariff Code:              | 8483.60.8000                                   |
| Seating Torque:               | 16 Nm                                            | Screw Material:           | Alloy Steel                                    |
| Dynamic Torque Reversing:     | 112.5 lb-in (12.73 Nm)                           | Screw Finish:             | Black Oxide                                    |
| Torsional Stiffness:          | 769 lb-in/Deg (86.9 Nm/Deg)                      | Forged Clamp Screw:       | M6                                             |
| Angular Misalignment:         | 2.0 deg                                          | ISO 9001:2015:            | Certified                                      |
| Parallel Misalignment:        | 0.012 in (0.30 mm)                               | REACH:                    | Compliant                                      |
| Axial Motion:                 | 0.030 in (0.76 mm)                               | RoHS3:                    | Compliant                                      |
| Recommended Hex Key:          | Metric Hex Keys                                  | Conflict Minerals:        | Compliant                                      |
| B1 Min Shaft Penetration:     | 0.600 in (15.2 mm)                               | B2 Min Shaft Penetration: | 0.600 in (15.2 mm)                             |

COMPONENT

Disc Coupling - Double



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**DCD36-7/8"-15MM-A**  
**Ruland**  
0.8750" X 15mm Bores, 2.250" (57.2mm)  
Od, And 3.080" (78.2mm) Length, Clamp  
Double Disc Coupling, Accommodates All  
Types Of Misalignment, Anodized  
Aluminum Hubs, Stainless Steel Disc  
Springs, And A Center Spacer

|             |
|-------------|
| UNIT        |
| Inch/Metric |
| SHEET       |