



|                               |                                                  |                           |                       |
|-------------------------------|--------------------------------------------------|---------------------------|-----------------------|
| O.D. (D):                     | 2.750 in (69.9 mm)                               | Hex Wrench Size:          | 6.0 mm                |
| Brand:                        | Ruland                                           | Number of Screws:         | 2 ea                  |
| Note:                         | Stainless steel hubs are available upon request. | Length (L):               | 3.531 in (89.7 mm)    |
| Static Torque:                | 850 lb-in                                        | B2 Max Shaft Penetration: | 1.650 in              |
| Maximum Speed:                | 10000 RPM                                        | Material:                 | Aluminum              |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)                   | Bore (B1):                | 1.0000 in             |
| Country of Origin:            | USA                                              | Bore (B2):                | 0.7500 in             |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in                          | Keyway:                   | No                    |
| Balanced Design:              | Yes                                              | B1 Max Shaft Penetration: | 1.650 in              |
| UNSPC:                        | 31163008                                         | Bore Tolerance:           | +0.001 in / -0.000 in |
| Dynamic Torque Non-Reversing: | 425 in-lbs                                       | Tariff Code:              | 8483.60.8000          |
| Seating Torque:               | 39 Nm                                            | Screw Material:           | Alloy Steel           |
| Dynamic Torque Reversing:     | 212.5 lb-in                                      | Screw Finish:             | Black Oxide           |
| Torsional Stiffness:          | 1600 lb-in/Deg                                   | Forged Clamp Screw:       | M8                    |
| Angular Misalignment:         | 2.0 deg                                          | ISO 9001:2015:            | Certified             |
| Parallel Misalignment:        | 0.012 in                                         | REACH:                    | Compliant             |
| Axial Motion:                 | 0.030 in                                         | RoHS3:                    | Compliant             |
| Recommended Hex Key:          | Metric Hex Keys                                  | Conflict Minerals:        | Compliant             |
| B1 Min Shaft Penetration:     | 0.750 in                                         | B2 Min Shaft Penetration: | 0.750 in              |

COMPONENT

Disc Coupling - Double



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**DCD44-16-12-A**  
**Ruland**  
1.0000" X X 0.7500" Bores, 2.750" Od, And  
3.531" Length, Clamp Double Disc  
Coupling, Accommodates All Types Of  
Misalignment, Anodized Aluminum Hubs,  
Stainless Steel Disc Springs, And A  
Center Spacer

|       |
|-------|
| UNIT  |
| Inch  |
| SHEET |