



| | | | |
|-------------------------------|--|---------------------------|--|
| O.D. (D): | 2.750 in (69.9 mm) | Seating Torque: | 39 Nm |
| Brand: | Ruland | Tariff Code: | 8483.60.8000 |
| Note: | Stainless steel hubs are available upon request. | Length (L): | 3.531 in (89.7 mm) |
| Static Torque: | 850 lb-in (96.0 Nm) | Keyway (K2): | 8 mm |
| Hex Wrench Size: | 6.0 mm | Material: | Aluminum |
| Maximum Speed: | 10000 RPM | Bore (B1): | 1.3750 in |
| Temperature: | -40°F to 200°F (-40°C to 93°C) | Bore (B2): | 24 mm |
| Country of Origin: | USA | Keyway: | Yes |
| Shaft Tolerance: | +0.0000 in / -0.0005 in +0.000 mm / -0.013 mm | Keyway (K1): | 5/16 in |
| Balanced Design: | Yes | B1 Max Shaft Penetration: | 1.650 in (41.9 mm) |
| UNSPC: | 31163008 | Conflict Minerals: | Compliant |
| Dynamic Torque Non-Reversing: | 425 in-lbs (48.01 Nm) | B2 Max Shaft Penetration: | 1.650 in (41.9 mm) |
| Number of Screws: | 2 ea | Bore Tolerance: | +0.001 in / -0.000 in (+0.03 mm / -0.00 mm) |
| Dynamic Torque Reversing: | 212.5 lb-in (24.00 Nm) | Screw Material: | Alloy Steel |
| Torsional Stiffness: | 1600 lb-in/Deg (180.8 Nm/Deg) | Screw Finish: | Black Oxide |
| Angular Misalignment: | 2.0 deg | Forged Clamp Screw: | M8 |
| Parallel Misalignment: | 0.012 in (0.30 mm) | ISO 9001:2015: | Certified |
| Axial Motion: | 0.030 in (0.76 mm) | REACH: | Compliant |
| Recommended Hex Key: | Metric Hex Keys | RoHS3: | Compliant |
| B1 Min Shaft Penetration: | 0.750 in (19.1 mm) | B2 Min Shaft Penetration: | 0.750 in (19.1 mm) |

COMPONENT

Disc Coupling - Double



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DCDK44-1 3/8"-24MM-A

Ruland

1.3750" X X 24mm Bores, 2.750" (69.9mm)
Od, And 3.531" (89.7 Mm) Length, 5/16" X
8mm Keyways, Clamp Double Disc
Coupling, Anodized Aluminum Hubs,
Stainless Steel Disc Springs, And A
Center Spacer

UNIT

Inch/Metric

SHEET