




Brand	Ruland
Conflict Minerals	Compliant
O.D. (D)	0.590 in (15.0 mm)
Material	Aluminum
Bore (B1)	0.1875 in
Bore (B2)	0.1250 in
Keyway	No
B2 Max Shaft Penetration	0.354 in
Bore Tolerance	+0.001 in / -0.000 in
B1 Max Shaft Penetration	0.354 in
Screw Material	Alloy Steel
Screw Finish	Black Oxide
Forged Clamp Screw	M2
ISO 9001:2015	Certified
REACH	Compliant
RoHS3	Compliant
Note	Stainless steel hubs are available upon request.
Length (L)	0.719 in (18.3 mm)
UNSPC	31163008
Static Torque	15 lb-in
Hex Wrench Size	1.5 mm
Maximum Speed	10000 RPM
Temperature	-40°F to 200°F (-40°C to 93°C)
Country of Origin	USA
Shaft Tolerance	+0.0000 in / -0.0005 in
Balanced Design	Yes
Number of Screws	2 ea
Tariff Code	8483.60.8000
Dynamic Torque Non-Reversing	7.5 lb-in
Dynamic Torque Reversing	3.75 lb-in
Torsional Stiffness	50 lb-in/Deg
Angular Misalignment	0.5 deg
Parallel Misalignment	0.00 in
Axial Motion	0.002 in
Seating Torque	0.6 Nm
Recommended Hex Key	Metric Hex Keys



COMPONENT

Disc Coupling - Single



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587 1-800-228-8895,
510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DCS10-3-2-A
Ruland
0.1875" X 0.1250" Bores, 0.590" Od, And 0.719" Length, Clamp
Single Disc Coupling, Accommodates Angular Misalignment And
Axial Motion, Anodized Aluminum Hubs, Stainless Steel Disc
Springs

UNIT

Inch

SHEET