



|                               |                                                  |                           |                                                |
|-------------------------------|--------------------------------------------------|---------------------------|------------------------------------------------|
| O.D. (D):                     | 1.313 in (33.3 mm)                               | Seating Torque:           | 2.1 Nm                                         |
| Brand:                        | Ruland                                           | Tariff Code:              | 8483.60.8000                                   |
| Note:                         | Stainless steel hubs are available upon request. | Length (L):               | 1.313 in (33.3 mm)                             |
| UNSPC:                        | 31163008                                         | B1 Max Shaft Penetration: | 0.842 in (21.4 mm)                             |
| Hex Wrench Size:              | 2.5 mm                                           | Material:                 | Aluminum                                       |
| Maximum Speed:                | 10000 RPM                                        | Bore (B1):                | 0.5000 in                                      |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)                   | Bore (B2):                | 11 mm                                          |
| Country of Origin:            | USA                                              | Keyway:                   | No                                             |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in<br>+0.000 mm / -0.013 mm | B2 Max Shaft Penetration: | 0.842 in (21.4 mm)                             |
| Balanced Design:              | Yes                                              | Conflict Minerals:        | Compliant                                      |
| Static Torque:                | 100 lb-in (11.3 Nm)                              | Bore Tolerance:           | +0.001 in / -0.000 in<br>(+0.03 mm / -0.00 mm) |
| Number of Screws:             | 2 ea                                             | Screw Material:           | Alloy Steel                                    |
| Dynamic Torque Non-Reversing: | 50 lb-in (5.65 Nm)                               | Screw Finish:             | Black Oxide                                    |
| Dynamic Torque Reversing:     | 25 lb-in (2.83 Nm)                               | Forged Clamp Screw:       | M3                                             |
| Torsional Stiffness:          | 313 lb-in/Deg (35.4 Nm/Deg)                      | ISO 9001:2015:            | Certified                                      |
| Angular Misalignment:         | 1.0 deg                                          | REACH:                    | Compliant                                      |
| Parallel Misalignment:        | 0.000 in (0.00 mm)                               | RoHS3:                    | Compliant                                      |
| Axial Motion:                 | 0.008 in (0.20 mm)                               | Recommended Hex Key:      | Metric Hex Keys                                |

COMPONENT

Disc Coupling - Single



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**DCS21-1/2"-11MM-A**  
**Ruland**  
0.5000" X 11mm Bores, 1.313" (33.3mm) Od,  
And 1.313" (33.3mm) Length, Clamp Single  
Disc Coupling, Accommodates Angular  
Misalignment And Axial Motion, Anodized  
Aluminum Hubs, Stainless Steel Disc  
Springs

|             |
|-------------|
| UNIT        |
| Inch/Metric |
| SHEET       |