




|                               |                                                  |                           |                       |
|-------------------------------|--------------------------------------------------|---------------------------|-----------------------|
| O.D. (D):                     | 2.250 in (57.2 mm)                               | Seating Torque:           | 16 Nm                 |
| Brand:                        | Ruland                                           | Tariff Code:              | 8483.60.8000          |
| Note:                         | Stainless steel hubs are available upon request. | Length (L):               | 2.313 in (58.8 mm)    |
| UNSPC:                        | 31163008                                         | B1 Max Shaft Penetration: | 1.085 in              |
| Hex Wrench Size:              | 5.0 mm                                           | Material:                 | Aluminum              |
| Maximum Speed:                | 10000 RPM                                        | Bore (B1):                | 0.8750 in             |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)                   | Bore (B2):                | 0.5000 in             |
| Country of Origin:            | USA                                              | Keyway:                   | No                    |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in                          | B2 Max Shaft Penetration: | 1.085 in              |
| Balanced Design:              | Yes                                              | Conflict Minerals:        | Compliant             |
| Static Torque:                | 450 lb-in                                        | Bore Tolerance:           | +0.001 in / -0.000 in |
| Number of Screws:             | 2 ea                                             | Screw Material:           | Alloy Steel           |
| Dynamic Torque Non-Reversing: | 225 lb-in                                        | Screw Finish:             | Black Oxide           |
| Dynamic Torque Reversing:     | 112.5 lb-in                                      | Forged Clamp Screw:       | M6                    |
| Torsional Stiffness:          | 1000 lb-in/Deg                                   | ISO 9001:2015:            | Certified             |
| Angular Misalignment:         | 1.0 deg                                          | REACH:                    | Compliant             |
| Parallel Misalignment:        | 0.00 in                                          | RoHS3:                    | Compliant             |
| Axial Motion:                 | 0.015 in                                         | Recommended Hex Key:      | Metric Hex Keys       |

|           |                        |
|-----------|------------------------|
| COMPONENT | Disc Coupling - Single |
|-----------|------------------------|



**Pacific International Bearing, Inc.**  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**DCS36-14-8-A**  
**Ruland**  
0.8750" X 0.5000" Bores, 2.250" Od, And  
2.313" Length, Clamp Single Disc Coupling,  
Accommodates Angular Misalignment  
And Axial Motion, Anodized Aluminum  
Hubs, Stainless Steel Disc Springs

|       |
|-------|
| UNIT  |
| Inch  |
| SHEET |