




O.D. (D):	1.625 in (41.3 mm)	Number of Screws:	2 ea
Brand:	Ruland	Conflict Minerals:	Compliant
Note:	Stainless steel hubs are available upon request.	Length (L):	1.563 in (39.7 mm)
Balanced Design:	Yes	Keyway (K2):	3/32 in
Seating Torque:	4.6 Nm	Material:	Aluminum
Hex Wrench Size:	3.0 mm	Bore (B1):	17 mm
Maximum Speed:	10000 RPM	Bore (B2):	0.3750 in
Temperature:	-40°F to 200°F (-40°C to 93°C)	Keyway:	Yes
Country of Origin:	USA	Keyway (K1):	5 mm
Shaft Tolerance:	+0.0000 in / -0.0005 in +0.000 mm / -0.013 mm	B1 Max Shaft Penetration:	0.755 in (19.2 mm)
UNSPC:	31163008	RoHS3:	Compliant
Tariff Code:	8483.60.8000	B2 Max Shaft Penetration:	0.755 in (19.2 mm)
Static Torque:	180 lb-in (20.3 Nm)	Bore Tolerance:	+0.001 in / -0.000 in (+0.03 mm / -0.00 mm)
Dynamic Torque Non-Reversing:	90 lb-in (10.15 Nm)	Screw Material:	Alloy Steel
Dynamic Torque Reversing:	45 lb-in (5.08 Nm)	Screw Finish:	Black Oxide
Torsional Stiffness:	625 lb-in/Deg (70.6 Nm/Deg)	Forged Clamp Screw:	M4
Angular Misalignment:	1.0 deg	ISO 9001:2015:	Certified
Parallel Misalignment:	0.000 in (0.00 mm)	REACH:	Compliant
Axial Motion:	0.010 in (0.25 mm)	Recommended Hex Key:	Metric Hex Keys

COMPONENT

Disc Coupling - Single



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DCSK26-17MM-3/8"-A
Ruland
17mm X 0.3750" Bores, 1.625" (41.3mm) Od,
And 1.563" (39.7mm) Length, 5mm X 3/32"
Keyways, Clamp Single Disc Coupling,
Anodized Aluminum Hubs, Stainless Steel
Disc Springs

UNIT
Inch/Metric
SHEET