



Bore Diameter (d)	8 mm
Outside Diameter (D)	16 mm
Width (B)	5 mm
Closure	Metallic Shield Pressed
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Brand	NMB
Precision	Abec 1
Radial Clearance	P25 (Standard)
Flanged	Flanged
Lubrication	LY121 Kyodo Yushi SRL Grease
Dynamic Load(Cr)	362 lbs
Static Load(C0r)	161 lbs
Series	DDL

COMPONENT	METRIC SERIES SHIELDED
-----------	------------------------

DDL-1680HHRA1P25LY12 1 NMB 8 Mm X 16 Mm X 5 Mm, Miniature Instrument Deep, Groove Radial Ball Bearing, Non-removable Metallic Shield, Flanged	UNIT
	METRIC
	SHEET



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.