


| Bore Diameter (d) | 4 mm |
|----------------------|------------------------------|
| Outside Diameter (D) | 13 mm |
| Width (B) | 5 mm |
| Closure | Metallic Shield Pressed |
| Ring Material | AISI 440C Stainless Steel |
| Ball Material | AISI 440C Stainless Steel |
| Brand | NMB |
| Precision | Abec 3 |
| Radial Clearance | P25 (Standard) |
| Lubrication | LY121 Kyodo Yushi SRL Grease |
| Dynamic Load(Cr) | 294 lbs |
| Static Load(COr) | 110 lbs |
| Series | DDR |



COMPONENT

METRIC SERIES SHIELDED



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDR-1340HHRA3P25LY12

1

NMB 4mm X 13mm X 5mm, Miniature Instrument Deep, Groove Radial Ball Bearing, Non-removable Metallic Shield UNIT

METRIC

SHEET