



Bore Diameter (d)	4 mm
Outside Diameter (D)	16 mm
Width (B)	5 mm
Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Brand	NMB
Precision	Abec 1
Radial Clearance	P25 (Standard)
Lubrication	LY121 Kyodo Yushi SRL Grease
Dynamic Load(Cr)	390 lbs
Static Load(C0r)	151 lbs
Series	DDR

COMPONENT	METRIC SERIES SHIELDED
-----------	------------------------



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDR-1640HHRA1P25LY121 NMB 4.0 Mm X 16.0 Mm X 5.0 Mm, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields	UNIT
	METRIC
	SHEET