		۸ L	r d v	Li D	
Bore Diameter (d) .1875 in					
Outside Diameter (D)	.5000 in				
Width (B)	.1960 in				
Closure	Metallic Shield				
Ring Material	AISI 440C Stainless Steel	■ B ->			
Ball Material	AISI 440C Stainless Steel				
Brand	NMB				
Precision	Abec 3				
Radial Clearance	P25 (Standard)				
Lubrication	LY121 Kyodo Yushi SRL Grease				
Dynamic Load(Cr)	295 lbs				
Static Load(C0r)	110 lbs				
Series	DDR		COMPONENT	INCH SERIES SH	IELDED
PIB	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	DDR-3ZZEERA3P25LY121 NMB .1875in X .5000in X .1960 In, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields		UNIT
					SHEET