


| Bore Diameter (d) | .2500 in |
|----------------------|---------------------------|
| Outside Diameter (D) | .6250 in |
| Width (B) | .1960 in |
| Closure | Metallic Shield |
| Ring Material | AISI 440C Stainless Steel |
| Ball Material | AISI 440C Stainless Steel |
| Brand | NMB |
| Precision | Abec1 |
| Radial Clearance | P25 (Standard) |
| Lubrication | L01 Ester Oil |
| Dynamic Load(Cr) | 330 lbs |
| Static Load(COr) | 135 lbs |
| Series | R4 |



COMPONENT

INCH SERIES SHIELDED



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDR-4ZZEERA1P25L01

 NMB

.2500 In X .6250 In X .1960 In, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields, Extended Inner Ring UNIT

INCH

SHEET