



Bore Diameter (d)	3 mm
Outside Diameter (D)	8 mm
Width (B)	3 mm
Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Brand	NMB
Precision	Abec 3
Radial Clearance	P25 (Standard)
Lubrication	LY551 NMB Low Noise Grease
Dynamic Load(Cr)	126 lbs
Static Load(C0r)	40 lbs
Series	DDR

COMPONENT	METRIC SERIES SHIELDED
-----------	------------------------



Pacific International Bearing, Inc.  
 33258 Central Ave. Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
 info@pibsales.com  
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**DDR-830ZZRA3P25LY551**  
**NMB**  
 3 Mm X 8 Mm X 3 Mm, Miniature  
 Instrument Deep, Groove Radial Ball  
 Bearing, Two Metal Shields

UNIT

METRIC

SHEET