



Width (B)	.1562 in
Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Brand	NMB
Precision	Abec 3
Radial Clearance	P25 (Standard)
Flanged	Flanged
Lubrication	L01 Ester Oil
Dynamic Load(Cr)	144 lbs
Bore Diameter (d)	.1250 in
Series	DDRF
Static Load Cap (C0r)	51 lbs
O.D. (D)	.3750 in

COMPONENT	METRIC SERIES SHIELDED
-----------	------------------------



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDRF-2ZZRA3P25L01 NMB .1250 In X .3750 In X .1562 In, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields, Flanged, Flanged	UNIT
	METRIC
	SHEET