


Bore Diameter (d)	.1875 in
Outside Diameter (D)	.5000 in
Width (B)	.1960 in
Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Brand	NMB
Precision	Abec 3
Radial Clearance	P25 (Standard)
Flanged	Flanged
Lubrication	LY121 Kyodo Yushi SRL Grease
Dynamic Load(Cr)	295 lbs
Static Load(C0r)	110 lbs
Series	DDRF



COMPONENT

METRIC SERIES SHIELDED



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

## DDRF-3ZZRA3P25LY121

## **NMB**

.1875in X .5000in X .1960in, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields, Flanged UNIT

**METRIC** 

**SHEET**