		▲ D	► B ► A Li d	r Lo	
Bore Diameter (d)	.5000 in]	▼		
Outside Diameter (D)	.7500 in	1			
Width (B)	.1562 in	1			
Closure	Metallic Shield	▼			
Ring Material	AISI 440C Stainless Steel	r			
Ball Material AISI 440C Stainless Steel		•			
Brand	NMB	1			
Precision	Abec 3	1			
Radial Clearance	P25 (Standard)				
Lubrication	LY121 Kyodo Yushi SRL Grease				
Dynamic Load(Cr)	112 lbs	1			
Static Load(C0r)	24 lbs	1			
Series	DDRI]	COMPONENT	INCH SERIES SH	IELDED
	Pacific International Bearing, Inc.	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB	DDRI-1212ZZRA3P25LY121		UNIT
PIB 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com		makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or	NMB .5000in X .7500in X .1562in, Miniature Instrument Deep, Groove Radial Ball		INCH
	www.pibsales.com	specifications. You are solely responsible for the use of the file, information or specifications.	Bearing, Two Metal Shields		SHEET