


Bore Diameter (d)	.1250 in
Bore Diameter (u)	.1250 111
Outside Diameter (D)	.3750 in
Width (B)	.1406 in
Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Brand	NMB
Precision	Abec 1
Radial Clearance	P25 (Standard)
Lubrication	L01 Ester Oil
Dynamic Load(Cr)	127 lbs
Static Load(COr)	41 lbs
Series	DDRI



COMPONENT

**INCH SERIES SHIELDED** 



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

## DDRI-618ZZEERA1P25L01

 $\mathsf{NMB}$ 

.1250 In X .3750 In X .1406 In, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields, Extended Inner Ring UNIT

**INCH** 

**SHEET**