



O.D. (D):	0.625 in (15.9 mm)	Hex Wrench Size:	2.0 mm
Brand:	Ruland	Maximum Speed:	6000 RPM
Length (L):	1.000 in (25.4 mm)	Temperature:	-40°F to 350°F (-40°C to 176°C)
Material:	303 Stainless Steel	Country of Origin:	USA
Bore (B1):	0.2500 in	Product Group:	F-Series Six Beam Coupling
Bore (B2):	0.1875 in	Shaft Tolerance:	+0.0000 in / -0.0005 in
Keyway:	No	Zero-Backlash?:	Yes
B1 Max Shaft Penetration:	0.483 in	Balanced Design:	Yes
B2 Max Shaft Penetration:	0.483 in	UNSPC:	31163003
Bore Tolerance:	+0.001 in / -0.000 in	Clearance Diameter (C) MAX:	0.796 in
Screw Material:	Stainless Steel	Cap Screw:	M2.5
Screw Finish:	Black Oxide	Static Torque:	18 lb-in
ISO 9001:2015:	Certified	Dynamic Torque Non-Reversing:	9 lb-in
REACH:	Compliant	Dynamic Torque Reversing:	4.5 lb-in
RoHS3:	Compliant	Torsional Stiffness:	0.088 Deg/lb-in
Conflict Minerals:	Compliant	Angular Misalignment:	3.0 deg
Tariff Code:	8483.60.8000	Parallel Misalignment:	0.008 in
Number of Screws:	2 ea	Axial Motion:	0.005 in
Seating Torque:	1.21 Nm		

COMPONENT	F-Series Six Beam Coupling
-----------	----------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

FCR10-4-3-SS
Ruland
1/4"x3/16" Bores, 0.625" Od 1.000" Length,
Six Beam Coupling, Stainless Steel Clamp
Style

UNIT
Inch
SHEET