



O.D. (D):	0.625 in (15.9 mm)	Number of Screws:	2 ea
Brand:	Ruland	Length (L):	1.000 in (25.4 mm)
Forged Set Screw:	M4	B2 Max Shaft Penetration:	0.483 in (12.3 mm)
Maximum Speed:	6000 RPM	Material:	303 Stainless Steel
Temperature:	-40°F to 350°F (-40°C to 176°C)	Bore (B1):	5 mm
Country of Origin:	USA	Bore (B2):	0.1875 in
Product Group:	F-Series Six Beam Coupling	Keyway:	No
Shaft Tolerance:	+0.0000 in / -0.0005 in +0.000 mm / -0.013 mm	B1 Max Shaft Penetration:	0.483 in (12.3 mm)
Zero-Backlash?:	Yes	Bore Tolerance:	+0.001 in / -0.000 in (+0.025 mm / -0.000 mm)
UNSPC:	31163003	Tariff Code:	8483.60.8000
Seating Torque:	1.76 Nm	Screw Material:	Alloy Steel
Static Torque:	18.1 lb-in (2.04 Nm)	Screw Finish:	Black Oxide
Dynamic Torque Non-Reversing:	9 lb-in (1.02 Nm)	ISO 9001:2015:	Certified
Dynamic Torque Reversing:	4.5 lb-in (0.51 Nm)	REACH:	Compliant
Torsional Stiffness:	0.088 Deg/lb-in (0.78 Deg/Nm)	RoHS3:	Compliant
Angular Misalignment:	3.0 deg	Conflict Minerals:	Compliant
Parallel Misalignment:	0.008 in (0.20 mm)	Axial Motion:	0.005 in (0.13 mm)
Hex Wrench Size:	2.0 mm		

COMPONENT	F-Series Six Beam Coupling
-----------	----------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

FSR10-5MM-3/16"-SS

Ruland

5mm X 3/16" Bores, 0.625" Od 1.000"
Length, Six Beam Coupling, Stainless
Steel Set Screw Style

UNIT
Inch/Metric
SHEET