



O.D. (D):	2.750 in (69.9 mm)	Dynamic Torque Reversing:	26.13 Nm
Brand:	Ruland	Hex Wrench Size:	6.0 mm
Maximum Speed:	10000 RPM	Screw Finish:	Black Oxide
Zero-Backlash?:	Yes	Material:	Aluminum
Balanced Design:	Yes	Bore (B1):	20 mm
UNSPC:	31163018	Bore (B2):	20 mm
Cap Screw:	M8	Keyway:	No
Static Torque:	104.5 Nm	B1 Max Shaft Penetration:	40.2 mm
Dynamic Torque Non-Reversing:	52.25 Nm	B2 Max Shaft Penetration:	40.2 mm
Temperature:	-40°F to 200°F (-40°C to 93°C)	Screw Material:	Alloy Steel
Angular Misalignment:	2.0 deg	Bore Tolerance:	+0.03 mm / -0.00 mm
Torsional Stiffness:	237 Nm/Deg	Length (L):	3.431 in (87.1 mm)
Parallel Misalignment:	0.30 mm	ISO 9001:2015:	Certified
Axial Motion:	0.76 mm	REACH:	Compliant
Bellows Attachment Method:	Epoxy	RoHS3:	Compliant
Length Tolerance:	+/- 0.76 mm	Conflict Minerals:	Compliant
Recommended Hex Key:	Metric Hex Keys	Tariff Code:	8483.60.8000
B1 Min Shaft Penetration:	19.1 mm	Number of Screws:	2 ea
Product Group:	Bellows Coupling Standard Length	Seating Torque:	39 Nm
Shaft Tolerance:	+0.000 mm / -0.013 mm	B2 Min Shaft Penetration:	19.1 mm

COMPONENT	Bellows Coupling Standard Length
-----------	----------------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

MBC70-20-20-A
Ruland
20mm X 20mm Bores, 69.9mm, Od,
87.1mm Length, Bellows Coupling, High
Stiffness, Aluminum

UNIT

Metric

SHEET